CALIPER CHECKER



Technical Specifications

Model	Measuring Steps	Overall Accuracy
CC1-300	20,50,100,150,200,250,300	±0.005mm
CC2-600	20, 50, 100,150,200,250,300,350,400, 450, 500, 550, 600	±0.005mm
CC3-1000	20,50,100,150,200,250,300, 350,400,450, 500,550,600,650,700, 750,800,850,900, 950,1000	±0.010mm

INTERNAL MICROCHECKER



Technical Specifications

Specifications	IM-300	IM-600
Range	25-300 mm	25-600 mm
Block Pitch	25 mm	25 mm
Accuracy	±3 μm	±5 μm

Features

- Gauge Blocks are made of Alloy Steel and are hardened, lapped and subzero treated for dimensional stability and housed in rigid housing, which enables ease of zero setting of inside micrometers in increments of 25mm
- It includes a set of two, 10mm gauge blocks and positioning pieces

Applications

Specially designed for zero setting of rod type inside micrometers



Accurate Metrology And Automation Company

(Formerly "Aditya Engineering Company")

Head Office : 67, Hadapsar Industrial Estate, Pune-411 013, Maharashtra, India.
+91-20- 6606 9595, +91 86000 23615

- 💡 Works : A/P Khalad, Saswad Jejuri Road, Tal. Purandhar, Pune-412 301, India.
- 🐛 +91 99700 02528 | 🖾 amac@accuratemetrology.in | 🛛 GST : 27AACFA5688G1ZA
- 💪 +91 86000 21671 | 🌐 www.accuratemetrology.in 🕴 PAN : AACFA5688G

Features

- Hardened and ground steel blocks
- Sub-Zero treated for Dimensional stability
- Each Gauge Block stacked in the rigid housing
- Can be used vertically and horizontally
- Available in range of 300, 600, 1000 mm
- Available in Inch version on request

Applications

• Calibration of all kind of Calipers & Height Gauges for measuring Height / Outside / Inside parameters



DEPTH MICROCHECKER

Features

- The Gauge Blocks are set in a rugged cast iron housing at increments of 25 mm to enable accurate resetting of the micrometer
- All gauge blocks are made of Alloy Steel hardened and sub-zero treated for dimensional stability
- A hardened, ground and lapped steel gauge block of 25mm is provided with the instrument, which serves as reference point for the calibration of depth micrometers at different heights

Applications :

Calibration and Zero setting of Depth Micrometres

Technical Specifications

Specifications	Model DM -150	Model DM - 300
Measuring Range	0-150 mm/6"	0-300 mm/12"
Graduations	25 mm/1"	25 mm/1"
Parallelism of Gauge Blocks	0.0015mm	0.0015 mm
Reference Block	25 mm/1" ± 0.5 mm	25 mm/1" ± 0.5 mm
Overall Accuracy	±0.002 mm/0.00008"	±0.003 mm/0.00012"

Authorised Distributor : **MKT-2024** Sales Branch Offices +91 99700 02573 : +91 80107 32455 Pune Delhi Nashik : +91 74474 64750 Bhiwadi : +91 95551 81100 Kolhapur : +91 86000 23613 : +91 95903 25411 Bengaluru Gujarat : +91 91759 83127 Chennai : +91 90214 12461 Kolkata : +91 99030 79509 Punjab : +91 95955 74755 Ch.Sambhajinagar : +91 99700 05605 : +91 76776 20966 Jamshedpu

Note : Due to continuous Improvements at our end, Specifications are subject to change without prior notice.